



Flo-Guard breathing filter

Bacterial and viral filter for CPAP and bilevel applications



Airway Management ▪ Breathing Filters

Flo-Guard

Low-resistance breathing filter for CPAP and bilevel

The Flo-Guard breathing filter is designed to be used at the machine end of a breathing system to protect the patient and machine against cross contamination, whilst maintaining a low resistance across a wide range of flow rates.

The Flo-Guard offers an excellent bacterial and viral filtration efficiency whilst offering the lowest resistance to flow available at very high flow rates.

The low resistance makes it an ideal filter for use in both the hospital and the home where high flow rates may potentially be used, this includes CPAP, bilevel and cough assist applications.



Electrostatic filter media

Providing an excellent filtration efficiency

Large surface area

To reduce resistance to flow

Clear housing

For good visibility

Conical shape

To aid airflow

Code	Description	Box Qty.
1690000	Flo-Guard breathing filter	50

Resistance to flow characteristics

Code	1690000
Bacterial and viral filtration efficiency	>99.99%
Compressible volume	80ml
Weight	28g
Connectors	22F-22M

Flow rate	Resistance to flow
30L/min	0.4 cm H ₂ O
60L/min	0.8cm H ₂ O
90L/min	1.4cm H ₂ O
120L/min	2.0cm H ₂ O
150Lmin	2.7cm H ₂ O
180L/min	3.4cm H ₂ O
210L/min	4.3cm H ₂ O
240L/min	5.1 cm H ₂ O

IS12.19 NL • Issue 2 11.15



Intersurgical Nederland B.V, Vluchtoord 28, 5406 XP, Uden, Nederland
 T: 0413 243 860 F: 0413 243 869 info@intersurgical.nl www.intersurgical.nl

UK • Ireland • France • Germany • Spain • Portugal • Italy
 Netherlands • Sweden • Denmark • Lithuania • Russia
 Czech Republic • Turkey • South Africa • China • Japan
 Taiwan • Philippines • USA • Colombia • Australia



Intersurgical Ltd is certified to ISO 14001, ISO 9001 and ISO 13485

Please think before you print
 Save energy and paper.
 If you must print this e-mail
 please print it double sided